



ACRYLIC PRIMER



2016-07-04

APPLICATION/CHARACTERISTICS:

DLX P-30 primer is used to prepare adhesive undercoat before finish coat is applied. It is a universal, multi-surface undercoat that can be used on mineral surfaces of all types. DLX P-30 primer is efficient and easy to use.

SUBSTRATE PREPARATION:

Uniformly apply plaster undercoat DLX P-30 to the prepared surface by means of a paint brush or a roll. The undercoat should not be applied in the temperature of less than +5°C. You can render the surface after the mix dries off completely, i.e. after about 5 to 6 hours.

PREPARATION:

DLX P-30 primer is delivered as ready-to-use product. It is not allowed to dilute it, thicken it or mix it with other products. After opening the bucket, its content must be stirred thoroughly to obtain homogenous consistency. The surface must be solid, even, cleaned, free from dust, lime coating, fat, oil, wax, or paint residues (chalk, lime, emulsion and oil paint). Main irregularities must be evened before. Surfaces of high dampness must be dried before render works. Never apply primer on frozen surfaces.

COVERAGE:

Approx. 0.2 l per 1 m².

STORING AND TRANSPORT:

DLX P-30 primer should be transported and stored in tight sealed buckets, in the temperatures above zero. It must be protected against overheating. Never leave the bucket open or spare the rest of the product for future application.

Date of expiration: 12 months from the date of manufacture.

DATE OF MANUFACTURE/COLOUR: given on the package.

PACKAGING:

5 L bucket; 72 buckets per pallet, 360 L;

10 L bucket; 44 buckets per pallet, 440 L.

TECHNICAL PARAMETERS:

Ingredients	water dispersion, synthetic resins and mineral fillers
Colour	white or colour
Density	about 1.4 kg/dm ³
Application temperature	+5°C to +25°C
Drying time	about 4 hrs
Consumption	About 0.2 L/m ² depending on the substrate absorption
Technical specification	ETA 15/0311 dated 29/05/2015

THIS PRODUCT IS THE PART OF

